



SERVO VOLTAGE CONTROLLER - 3 PHASE

Technical Index

| | |
|-------------------------|---|
| Input voltage | 160-250V |
| Phase | Single-phase |
| Frequency | 50-60HZ |
| Adjusting time | <1S(When input voltage has a change of 10%) |
| Max of | 0.5KVA 1KVA 1.5KVA 2KVA 3KVA 5KVA 10KVA 15KVA 20KVA 30KVA |
| Output current | 2A 4A 6.5A 8A 12A 20A 40A 60A 80A 120A |
| Protection over voltage | 245±5V |
| Delay | Short Deley3-7 sec long Delay 3-7min |
| Ambient temperature | -5~+40°C |
| Temperature rise | <60°C(full load) |
| Relative humidity | <90°C |
| Wave form distortion | No wave form distortion |
| Efficiency | >95% |
| Insulation resistance | ≥2MΩ |

Specifications and Model

| Model | Unit | Package size(cm) | Weight(kg) |
|---------|------|------------------|------------|
| 500VA | 4 | 44×25×33 | 4.5 |
| 1000VA | 4 | 49×28×39 | 5.5 |
| 2000VA | 2 | 60×36×25 | 10.2 |
| 3000VA | 2 | 60×38×30 | 12 |
| 5000VA | 1 | 54×29.5×30.5 | 22.5 |
| 10000VA | 1 | 34.5×29.5×54 | 35 |
| 15000VA | 1 | 49.2×41×87 | 45 |
| 20000VA | 1 | 49.2×41×87 | 75 |